

TIMBERWOLF Firewood Processor Comparison Chart



*Specs subject to change without notice.

MODEL	TW-PRO MP	PRO-MX Inline	PRO-HD Inline	PRO-HD XL Inline
POWER PLANT	36 HP Yanmar Diesel	49 HP John Deere Diesel	80 HP John Deere Diesel	80 HP John Deere Diesel
PUMP (gpm)	22-22	22-22	33-20-13	33-20-13
WEIGHT (lbs.)	5,560	6,500	8,500	9,000
SAW (in.) / CHAIN GAUGE	25 Hydraulic / .404	25 Hydraulic / .404	25 Hydraulic / .404	25 Hydraulic / .404
TOP ROLL CLAMPING SYSTEM	STD	STD	STD	STD
SPLITTER CYLINDER DIA. (in.)	4	4	5	5
MAX. LOG DIA. (in.)	18	22	22	22
TROUGH LENGTH (ft.)	10 STD	16 STD	16 STD	16 STD
MAX. LOG LENGTH (ft.)	14	20	20	20
HYDRAULIC CAPACITY (gal.)	40	65	65	65
LIVE DECK (Electric Winch)	STD	STD	STD	STD
LIVE DECK (Hydraulic)	N/A	OPT	OPT	OPT
DECK SIZE (ft.)	8 (deep) x 6 (wide)	8 (deep) x 12 (wide)	8 (deep) x 12 (wide)	8 (deep) x 12 (wide)
HYDRAULIC LIFT ARMS	N/A	N/A	N/A	N/A
HYDRAULIC OIL COOLER	N/A	OPT	OPT	STD
ELECTRIC AUTO CYCLE	N/A	OPT	OPT	STD
CYCLE TIME (sec.)	10	10	7	4.5
4-WAY WEDGE	STD	STD	OPT	OPT
6-WAY WEDGE	OPT	OPT	STD	OPT
8-WAY WEDGE	N/A	N/A	OPT	STD
DOT LIGHTS	STD	STD	STD	STD