

TIMBERWOLF Log Splitter Comparison Chart



¹Specs subject to change without notice. ²Available in 36" and 48" lengths. *Include 4-way wedge.
 ** 6-way box wedge and regular 2-way wedge come standard; 4, 6-way wedges are optional.

MODEL	TW-P1	TW-HV1	TW-HV2	TW-2	TW-2HD	TW-2/36	TW-3	TW-3HD ²	TW-S3	TW-5 ²	TW-5FC	TW-6	TW-7	TW-10
WEIGHT	475	675	775	575	875	765	450	725*	575	950*	950*	1,475*	1,675	10,350
SPLITTING (tons)	20	20	25	20	20	20	17	22	18-20	25	20	28	28	50
ENGINE (h.p.)	5.5	5.5	9	9	9	9	N/A	N/A	N/A	11	11	18	18	49
PUMP (gpm)	11	11	16	16	16	16	20	20	N/A	22	22	22	22	30
HYDRAULIC TANK CAPACITY-GALLONS	4.5	7.5	7.5	7.5	15	7.5	15	15	N/A	15	15	20	20	70
MAX. LOG LENGTH	26	24.5	24.5	26	26	36	26	26	30	26	26	26	26	120
CYLINDER SIZE (in.)	24x4x1½	24x4x2	24x5x2	24x4x2	24x4x2	35x4x2	24x4x2	24x5x2	30x4x2	24x5x2	24x4x2	24x5x3.5	24x5x3.5	96x8x5
CYCLE TIME (sec.)	13	13	10	9	9	14	6	10	8-12	10	6	8	8	72
FRAME (in.)	5	5"	5"	5"	6.5"	5"	5"	6.5"	7"	6.5"	6.5"	6.5"	12"	12"
HITCH (in.)	2	2"	2"	2"	2"	2"	N/A	N/A	N/A	2"	2"	2"	2"	2 5/16"
4-WAY WEDGE	OPT	N/A	N/A	OPT	OPT	OPT	OPT	STD	N/A	STD	STD	STD	**	STD
6-WAY WEDGE	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OPT	N/A	OPT	N/A	OPT	**	N/A
LOG LIFT	OPT	N/A	N/A	OPT	OPT	OPT	OPT	OPT	N/A	OPT	OPT	OPT	OPT	N/A
TABLE GRATE	OPT	N/A	N/A	OPT	OPT	OPT	OPT	OPT	N/A	OPT	OPT	OPT	OPT	N/A
AUTO CYCLE	N/A	N/A	N/A	N/A	OPT	N/A	N/A	OPT	N/A	STD	STD	STD	STD	OPT
WEDGE LIFT	N/A	N/A	N/A	N/A	OPT	N/A	N/A	OPT	N/A	STD	STD	STD	OPT	N/A
WHEEL (in.)	8	8"	12"	8"	12"		N/A	N/A	N/A	12"	12"	13"	13"	16"