

TIMBERWOLF MANUFACTURING CORP. PRODUCT SPECIFICATIONS

SPLITTER MODEL	WEIGHT	SPLITTING TONS	ENGINE H.P.	PUMP GPM	HYDRAULIC TANK CAPACITY - GALLONS	MAX LOG LENGTH	CYLINDER SIZE	CYCLE TIME	FRAME	HITCH	4 WAY WEDGE	6 WAY WEDGE	LOG LIFT	LOG CRADLES	AUTO CYCLE	WEDGE LIFT	FENDERS	AVAILABLE IN 36" & 48" LENGTHS	3 POINT HITCH MACHINE	PTO DRIVEN	DRIVEN FROM TRACTOR HYDRAULICS
TW-P1 BRIGGS	375	20	5	11	4.5	26	24X4X1¾	13	5"	2"	OPT	N/A	N/A	STD	N/A	N/A	N/A				
TW-P1 HONDA	375	20	5.5	11	4.5	26	24X4X1¾	13	5"	2"	OPT	N/A	N/A	STD	N/A	N/A	N/A				
TW-2	525	20	9	16	7.5	26	24X4X2	11	5"	2"	OPT	N/A	N/A	STD	N/A	N/A	N/A				
TW-2 HD	650	20	9	16	15	26	24X4X2	11	6.5"	2"	OPT	OPT	OPT	STD	OPT	OPT	OPT	L			
TW-3	300	20	N/A	20	7.5	26	24X4X2	6	5"	N/A	OPT	N/A	N/A	STD	OPT	N/A	N/A		O	P	
TW-3 HD	525	25	N/A	20	15	26	24X5X2	10	6.5"	N/A	STD	OPT	OPT	STD	OPT	OPT	N/A	L	O	P	
TW-5	850	25	11	22	15	26	24X5X2	10	6.5"	2"	STD	OPT	OPT	STD	STD	STD	OPT	L			
TW-5 FC	850	20	11	22	15	26	24X4X2	6	6.5"	2"	STD	N/A	OPT	STD	STD	STD	OPT	L			
TW-6	1270	28	18	22	20	26	24X5X3.5	8	6.5"	2"	STD	OPT	OPT	STD	STD	STD	OPT	L			
TW-10	10550	56	47	30	40	96	96X8X4	60	12"	2 5/16"	STD	N/A	N/A	STD	OPT	N/A	STD				P

FC=FAST CYCLE

*Depends on tractor hydraulics

CONVEYOR MODEL	BELT WIDTH	MAX. HEIGHT	RETRACT. HEIGHT	5.5 HP HONDA GR BELT DRIVE	5.5 HP HONDA HYDRAULIC	POWER BY PROCESOR HYDRAULICS	LOW CLOG WING PULLEY DRIVE DRUM	RUFF TOP BELTING	RUFF TOP W/T CLEATS	CHAIN DRIVE WITH CLEATS	BELT SPEED	COUPLER	CHIP SEPARATOR	LIGHT KIT
20 FOOT	18"	11'	84"	STD	OPT	OPT	OPT	STD	OPT	N/A	2.2FT/SEC	2'	OPT	OPT
24 FOOT	18"	12'-6"	85"	STD	OPT	OPT	OPT	STD	OPT	N/A	2.2FT/SEC	2'	OPT	OPT
26 FOOT	18"	14'	92"	STD	OPT	OPT	OPT	STD	OPT	N/A	2.2FT/SEC	2"	OPT	OPT
30 FOOT HD	24"	15' - 4"	96"	N/A	STD	OPT	N/A	N/A	N/A	STD	VARIABLE	2"	OPT	OPT

GR=GEAR REDUCED